

Product data sheet

TS 5000 E-ISM

Overhead door closer system with guide rail for double leaf doors with closing sequence control and electric hold-open device



Product features

System comprising two door closers TS 5000 and an E-ISM guide rail
Closing force of EN2-6 with variable adjustment
Operating voltage 24 V DC
Can be used for right and left hand doors without conversion
Electric hold-open device in the guide rail with hold-open area of 80°-130°
Closing sequence control holds the active leaf in the waiting position until the passive leaf is closed
Hydraulic latching action which accelerates the door shortly before the closed position
Closing speed can be individually adjusted
Integrated back check, slows down doors that are thrown open forcefully
Visual closing force display for easy control of the setting
All functions can be adjusted from the front

Application Areas

Double-leaf single-action doors
Symmetrical and asymmetrical door division possible
Single-action doors up to 2800 mm hinge clearance and 1400 mm leaf width, overlength up to 3200 mm
Door leaf installation hinge side
Hold-open systems with integrated hold-open device

Product Data Table

Product features	GEZE TS 5000 E-ISM
Suitability for fire protection doors	Yes

Accessory

Product name

CB flex
Rauchschalterzentrale RSZ6 ECwire
ABDECKK TS 5500/4500
Smoke switch control unit RSZ 6
GEZE Rauchschalter GC 152
GEZE Rauchschalter GC 153
Aufputzdose 1-fach
Notöffnungstaster AS 500
GEZE GC 171 wireless module

Product name

GEZE GC 175 wireless input module

GEZE Funkrauchmelder GC 172

GEZE Funktemperaturmelder GC 173

GEZE Wireless KIT

Part

Product name

E-ISM Gleitschiene TS 5000

E-ISM Gleitschiene TS 5000 Überlänge

TS 5000 O. GLEITSCH.