

# Product data sheet

## TS 5000 L-ISM VPK

Overhead door closer system with guide rail, for opposite hinge side, for double leaf doors with anti-panic function and closing sequence control



### Product features

Complete package with two TS 5000 L and TS 5000 L-IS door closers with ISM guide rail
Closing force of EN2-6 with variable adjustment
Can be used for right and left hand doors without conversion
Full panic function on both door leaves up to x dimension 110 mm
Closing sequence control holds the active leaf in the waiting position until the passive leaf is closed
Hydraulic latching action which accelerates the door shortly before the closed position
Closing speed can be individually adjusted
Integrated back check, slows down doors that are thrown open forcefully
Visual closing force display for easy control of the setting
All functions can be adjusted from the front

### Application Areas

Fire and smoke protection doors
Double leaf single-action doors with panic function
Symmetrical and asymmetrical door division possible
Single-action doors up to 2800 mm hinge clearance and 1400 mm leaf width, for door weights up to 180 kg
Door leaf installation opposite hinge side

### Product Data Table

Product features	GEZE TS 5000 L-ISM VPK
Suitability for fire protection doors	Yes

### Accessory

<b>Product name</b>
GEZE CB flex
Mechanical hold-open unit

**Part**

<b>Product name</b>
TS 5000 L-ISM VPK
GEZE TS 5000 L-IS