

Product data sheet

TS 5000 R/O

Overhead door closer system with guide rail for single leaf doors up to 1400 mm width with smoke switch control unit and GEZE hold-open magnet



Product features

Closing force of EN2-6 with variable adjustment
Operating voltage 230 V AC
Can be used for right and left hand doors without conversion
Door is held open by a hold-open magnet or door closer with free swing function
Integrated smoke switch control unit, whose signal closes the door automatically in the event of a fire
Smoke switch with contamination indicator and adaption of the alarm threshold
Additional smoke detectors may be fitted
Hydraulic latching action which accelerates the door shortly before the closed position
Closing speed can be individually adjusted
Integrated back check, slows down doors that are thrown open forcefully
Visual closing force display for easy control of the setting
All functions can be adjusted from the front

Application Areas

Right and left single-action doors
Single-action doors up to 1400 mm leaf width
Door leaf installation hinge side
Hold-open systems with integrated smoke switch

Product Data Table

Product features	GEZE TS 5000 R/O
Suitability for fire protection doors	Yes

Accessory

Product name
Mechanische Öffnungsbegrenzung E-/R-/ISM
Sockel Bodenmontage für GEZE Haftmagnet
ABDECKK TS 5500/4500
GEZE Rauchschalter GC 152
GEZE Rauchschalter GC 153
Aufputzdose 1-fach
GEZE GC 171 wireless module
GEZE GC 175 wireless input module
GEZE Funkrauchmelder GC 172
GEZE Funktemperaturmelder GC 173

Product name

GEZE Wireless KIT

Part

Product name

Haftgegenplatte Basis

Haftgegenplatte mit Federpuffer

Haftgegenplatte mit Gelenk

Haftmagnet Grundmodell

Haftmagnet Flexibel

Haftmagnet Flexibel 335mm

Haftmagnet Wandmontage

Haftmagnet Wandmontage - 65 mm

Haftmagnet Wandmontage Aufputz

Haftmagnet Wandmontage Unterputz

R-Gleitschiene ohne E-Feststellung

TS 5000 O. GLEITSCH.

Notöffnungstaster AS 500