

# Product data sheet

## ECdrive T2-FR

Automatic linear sliding door system in escape and rescue routes for doors up to 140 kg leaf weight



### Product features

Slim design with a cover height of just 100 mm for greater creative freedom
With double roller carriage and GCprofile Therm up to 140 kg leaf weight
Connectivity via GEZE Cockpit
Efficient installation thanks to pre-drilled tracks and elongated holes
Full floor guide available for controlled diversion of rainwater
Integrated line-feeds make cable laying easier
Can be networked via CAN bus and integrated into building technology management systems
Independent error recognition and recording
Freely configurable inputs and outputs for different functions
Integrated rechargeable battery for emergency opening in the event of a power failure
Self-cleaning roller carriage reduces maintenance effort and costs
Various mechanical and electrical lockings are optionally available
Service interface for easy maintenance

### Application Areas

Single and double leaf sliding door systems in escape and rescue routes
Interior and exterior doors with high access frequency
All-in-one solution for entrance areas with GCprofile Therm and fanlight
If extra impermeability or energy efficiency are needed
Opening widths of 700 to 3000 mm possible
Door leaf weight of up to 140 kg per leaf
Suitable profile systems are fine-framed profile systems with ISO and mono glass, GCprofile Therm, ESG clamping profile, on-site frame and wooden leaves

### Product Data Table

Productname	ECdrive FR
For 1-leaf door systems	Yes
For 2-leaf door systems	Yes
Height	100 mm
Depth	190 mm
Leaf weight (max.)	120 kg
Leaf weight (max.) 1-leaf with GCprofile Therm	140 kg
Leaf weight (max.) 2-leaf	120 kg
Leaf weight (max.) 2-leaf with GCprofile Therm	140 kg
Opening width 1-leaf	700 mm 3000 mm
Opening width 1-leaf with GCprofile Therm	1500 mm
Opening width 2-leaf	900 mm 3000 mm
Opening width 2-leaf with GCprofile Therm	3000 mm

Operating temperature	-15 °C 50 °C
IP rating	IP20
Disconnection from mains	Main switch in the drive
Approvals	DIN 18650, EN 16005, DIN EN ISO 13849: Performance Level D, AutSchR

### Accessory

<b>Product name</b>
---------------------

GEZE GC 363
-------------