

Certificate of constancy of performance

No. 0672-CPR-0111

In compliance with *Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011* (the Construction Products Regulation or CPR), this certificate applies to the

Construction Product(s) **Sequential closing control**
„GEZE ISM-guide rail“ for overhead door closers
with the classification enclosed in the annex 1 of this certificate

placed on the market
under the name or trade
mark of

GEZE GmbH
Reinhold-Vöster-Str. 21-29
71229 Leonberg
Germany

produced in the
manufacturing plant(s)

Plant 01 and Plant 03

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in

Annex ZA
of the standard(s)

EN 1158:1997/A1:2002/AC:2006

under system

1

for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the

constancy of performance of the construction product.

This certificate was first issued on **13.12.2019** and will remain valid as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

This document has been translated for informative purpose only. Original version is issued in German. In any case of doubt the German version is valid.



Stuttgart, 29.10.2019

(Dr. rer. nat. Stefan Lehner)
Head of Certification Body



Deutsche
Akkreditierungsstelle
D-ZE-11027-05-00

Annex 1

to the certificate of constancy of performance No. 0672-CPR-0111

Classification of the guide rail ¹⁾

EN 1158

3	8 *	6 3	1	1	4
---	-----	--------	---	---	---

The following installation variant is possible:

- GEZE ISM-guide rail BG: assembly on opposite hinge side
- GEZE ISM-guide rail with pivot bearing: moving leaf is equipped with "GEZE TSA 160NT F" or "GEZE Slimdrive EMD-F"
fixed leaf is equipped with overhead door closer according to ¹⁾

¹⁾ The following overhead door closer types can be used in combination with this construction products: „GEZE TS 3000 V“, „GEZE TS 3000 EN3“, „GEZE TS 3000 EC“, „GEZE TS 3000 EC BC“, „GEZE TS 5000“, „GEZE TS 5000 S“, „GEZE TS 5000 L“, „GEZE TS 5000 IS“, „GEZE TS 5000 L IS“, „GEZE TS 5000 ECline“, „GEZE TS 5000 L ECline“, „GEZE TS 5000 EFS 3-6“ and „GEZE TS 5000 SoftClose“.

The manufacturer has to point out in the assembly and adjustment documents of the door closer, that the door closer should be at least on size 3 for use on fire/smoke door assemblies.

* The in footnote ¹⁾ listed overhead door closers are not door closers with an automatic door opening system (classification 8). Nevertheless, according to DIN EN 1158, chapter 7.2.7.5 the 500.000 cycles (necessary for classification 8) were completed in the way described in the standard.

Stuttgart, 08.08.2022

Material Testing Institute – University of Stuttgart
Department Fire Safety
Certification Body



(Dr. rer. nat. Andrea Bramborg-Kramer)
Deputy Head of the Certification Body

