

# Product data sheet

## TZ 300 SN AP

Door control unit for controlling individual escape route doors with key switch and power supply



### Product features

- Full-area operable impact cover enables fast and safe activation of the illuminated emergency button in panic situations
- Coloured supply terminals simplify installation
- Consistent design allows easy replacement with a networkable TZ 320
- Integrated signal transmitters can easily be extended by additional external signal transmitters
- Integrated power supply offers additional flexibility
- Integrated key switch enables authorised access to emergency exit

### Application Areas

- EItVTR-compliant protection of an emergency exit against unauthorised access
- Can be used on single and double leaf doors
- Integrated interface enables the emergency exit to be unlocked via a danger alarm system
- Surface mounting allows subsequent installation on the door with little effort

### Product Data Table

Product features	TZ 300 SN AP
Width	77 mm
Height	197 mm
Depth	88 mm
Operating voltage	24 V DC
Operating voltage	230 V
Current consumption	100 mA
Power supply for external devices	650 mA
Contact rating	30 V / 1 A
Sabotage contact	Yes
Number of inputs	1 Stk.
Number of outputs	1 Stk.
Emergency button	Yes
Visual display	yes
Acoustic signal	75 dB
Temperature range	-10 °C - 55 °C
IP rating	IP30
Type of installation	surface-mounting
Type of cylinder	Euro profile cylinder
With ribbon cable	Yes
EItVTR	Yes

### Accessory

Product name
SCT220
SCT 320 UP, key switch
SCT222